

50-Ohm Load

0 ... 4000 MHz

0.5 ... 100 W

- Standard 50-Ohm terminations for small and medium power
- Suitable for terminating open ports on RF equipment for indoor and /or outdoor applications

0.5 Watt *

Type No.	K 62 26 61 1
Connector	N male
Frequency range	0 – 2700 MHz
VSWR	
0 – 1000 MHz	< 1.08
1000 – 2000 MHz	< 1.15
2000 – 2700 MHz	< 1.20
Application	Indoor
Weight	40 g
Packing size	90 x 60 x 25 mm
Dimensions	33 / 21 mm diameter



K 62 26 61 1

1.5 Watt *

Type No.	784 10367	784 10470
Connector	7-16 male	7-16 female
Frequency range	0 – 4000 MHz	
VSWR		
0 – 2000 MHz	< 1.10	
2000 – 4000 MHz	< 1.30	
Application	Indoor or outdoor (IP65)	
Weight	120 g	
Packing size	Approx. 50 x 90 x 100 mm	
Dimensions	40 / 32 mm diameter	42 / 29 mm diameter



784 10367

2 Watt *

Type No.	K 62 26 11 1
Connector	N male
Frequency range	0 – 2700 MHz
VSWR	
0 – 1000 MHz	< 1.08
1000 – 2000 MHz	< 1.15
2000 – 2700 MHz	< 1.20
Application	Indoor
Weight	40 g
Packing size	90 x 60 x 25 mm
Dimensions	30 / 21 mm diameter



K 62 26 11 1

10 Watt *

Type No.	K 62 26 40 1	K 62 26 41 1
Connector	N female	N male
Frequency range	0 – 2700 MHz	
VSWR		
0 – 1000 MHz	< 1.08	
1000 – 2000 MHz	< 1.15	
2000 – 2700 MHz	< 1.20	
Application	Indoor	
Weight	Approx. 250 g	
Packing size	50 x 90 x 100 mm	
Dimensions (w x h x d)	40 x 82 x 77 mm (including connector)	40 x 82 x 85 mm (including connector)



K 62 26 40 1

50-Ohm Load

0 ... 4000 MHz

0.5 ... 100 W

25 Watt *


Type No.	K 62 26 20 1	K 62 26 21 1	K 62 26 20 7	K 62 26 21 7
Connector	N female	N male	7-16 female	7-16 male
Frequency range	0 – 2700 MHz			
VSWR	0 – 1000 MHz < 1.08 1000 – 2000 MHz < 1.15 2000 – 2700 MHz < 1.20			
Application	Indoor			
Weight	Approx. 0.5 kg			
Packing size	50 x 100 x 135 mm			
Dimensions (w x h x d)	35 x 94 x 113 mm (incl. connector)	35 x 94 x 121 mm (incl. connector)	35 x 94 x 125 mm (incl. connector)	35 x 94 x 124 mm (incl. connector)



K 62 26 20 1

50 Watt *

Type No.	K 62 26 30 1	K 62 26 31 1	K 62 26 30 7	K 62 26 31 7
Connector	N female	N male	7-16 female	7-16 male
Frequency range	0 – 2700 MHz			
VSWR	0 – 1000 MHz < 1.08 1000 – 2000 MHz < 1.15 2000 – 2700 MHz < 1.20			
Application	Indoor			
Weight	Approx. 0.8 kg			
Packing size	80 x 95 x 145 mm			
Dimensions (w x h x d)	67 x 90 x 130 mm (incl. connector)	67 x 90 x 138 mm (incl. connector)	67 x 90 x 134 mm (incl. connector)	67 x 90 x 133 mm (incl. connector)



K 62 26 30 1

100 Watt *

Type No.	K 62 26 50 1	K 62 26 51 1	K 62 26 50 7
Connector	N female	N male	7-16 female
Frequency range	0 – 1000 MHz		
VSWR	0 – 1000 MHz < 1.08		
Application	Indoor		
Weight	Approx. 2.4 kg		
Packing size	130 x 195 x 180 mm		
Dimensions (w x h x d)	114 x 153 x 156 mm (including connector)	114 x 161 x 156 mm (including connector)	114 x 170 x 156 mm (including connector)



K 62 26 50 1

* Rated power at 40 °C ambient temperature. The max. power rating increases or decreases with falling or rising ambient temperature.

Note: The 50-Ohm load, type 782 10474, should be used if intermodulation requirements are of high priority.